Minimal, Local, Causal Explanations for Jailbreak Success in Large Language Models

Shubham Kumar and Narendra Ahuja

UNIVERSITY OF ILLINOIS URBANA-CHAMPAIGN

COLM 2026

Intro & Motivation

Question: Why do jailbreak attacks succeed?



Motivation: Understanding why jailbreaks succeed may help us design better jailbreak defenses.

Prior Work: Global explanations for jailbreak success analyze intermediate representations:



Research Problem: How do we explain a single (local) instance of jailbreak success?

One Answer: Find the minimal change to x_j in the representation space that causes x_j to fail (i.e., induce a similar refusal response to x_o)

=> prior work makes the **same** change to **all** tokens.
We ask if we can come up with a more minimal change.

Credits: (1) Jailbreak figure: Xinyue Shen: https://arxiv.org/abs/2308.03825
(2) SAE figure: Nick Jiang: https://www.lesswrong.com/posts/8YnHuN55XJTDwGPMr/a-gentle-introduction-to-sparse-autoencoders
(3) Activation Patching: Mahesh Deshwal: https://www.linkedin.com/posts/deshwalmahesh_even-heard-about-activation-patching-in-activity-7350384806104358912-eQD-/

Preliminaries

How to make changes?

Activation Patching:



✔ within distribution ✔ token-specific changes

What to change?

Sparse Autoencoders (SAEs):



To make minimal, interpretable changes, we activation patch along concept vectors.

Method

1. Token Matching: Activation patching assumes same structure between both sequences. Not true in our case.

A prompt x to a chat model has the following components:

$$x = [T_{\text{sys}}, T_{\text{inst}}, T_{\text{post-inst}}]$$



(a) Token matching issue (b) Re-sample T_{inst}, then match (c) Final matching scheme

2. Algorithm: Performs iterative, token-specific activation patches along concept vector directions to minimize Δ in the first-output token prob. distributions.



Results

Main Benchmark: LOCA effectively induces refusal with minimal changes

Minimal Patches: # patches for patched output token == original prompt's output token
Refusal Rate: % of times that patched output token == original prompt's output token after all patches



(b) GEMMA-3 (a) LLAMA

Localization Analysis: Which tokens get selected for activation patches?

- Checked three layer depths (early, early-middle, and middle)
- *Location*: user instruction token vs. post-instruction token
- *Token Semantics:* punctuation vs. word



Location: user instruction tokens selected early; post-inst. selected later
Semantics: no bias early; punctuation selected layer

Paper **Project Page** **Linkedin**

Icons by Icons8